




BrightDrop Zevo 600  
3 Door Cargo Van  
2023 -



400V  
Li-ion

	Airbag		Stored gas inflator		Seat belt pretensioner		SRS control unit		Gas strut/ Preloaded spring
	High strength zone		Battery low voltage		High voltage battery pack		High voltage power cable component		Cable Cut Location

**DO NOT CUT ANY ORANGE COLORED HIGH VOLTAGE CABLES.**

Identification Number

2G5-22101

Version Number

2

Page Number

Page 1 of 4


## 1. Identification / recognition




Lack of engine noise does not mean vehicle is off: vehicle movement capability exists until vehicle is fully shut down.

Always wear appropriate PPE.


### Emblems and Badging



Hood Emblem




Side Badging



Rear Badging



### First Responder Information Label




## 2. Immobilization / stabilization / lifting

### IMMOBILIZE VEHICLE:

- Block the wheels.
- Press the Electric Parking Brake (EPB) switch momentarily. The red parking brake status light will flash and then stay on once the EPB is fully applied.
- Place the vehicle into Park mode:
  - 2023 Model Year** -- Press the button on top of the shift lever to shift to P (Park).
  - 2024 Model Year and later**-- Press the button at the end of the shift lever to shift to P (Park).



2023 Model Year



2024 Model Year and Later


### LIFTING POINTS:



There are features on the body of the vehicle, for use as primary lifting points.

The lifting point features should only be used for lifting the vehicle. Do NOT use these features as attachment points to move or tie the vehicle down.

Do NOT lift the vehicle from any locations on the high voltage battery.




## 3. Disable direct hazards / safety regulations




The vehicle is equipped with a battery management system with internal fault detection. In the event of a **"Battery Danger Detected"** notification, **DO NOT cut or disable the low voltage system**, unless you need to disable the airbags for occupant extrication.

### MAIN METHOD:

- Press the POWER button to disable vehicle propulsion.





2023 Model Year



2024 Model Year and Later

- Remove the outside rearview mirror cover:
  - Start at the bottom of the cover and pry out.
  - Release the tabs at the front and top of the cover.
  - Slide the cover forward to remove.
- Double cut the low voltage cable marked by the yellow tape. Ensure that the cuts are clean and that there is no risk of loose wires touching.



**This cut will disable the airbag and high voltage system.**

**DO NOT CUT ANY ORANGE COLORED HIGH VOLTAGE CABLES.**

Identification Number

2G5-22101

Version Number

2


Page Number

Page 2 of 4

## VEHICLE AT CHARGE STATION:

If able, terminate charging by removing the charge handle from the vehicle.

The common charge handle is shown; The DC Fast Charge handle is moderately larger and may require additional effort to disconnect.




## 4. Access to the occupants



Refer to the front page for illustrations high strength zones and specific safety related component locations.



- The windshield is made of Laminated Glass



- The front quarter and side pocket door windows are made of Tempered Glass




### Passenger Compartment Door Access


The inside and outside door handles are actuated by rotating the top of the handle from the front to the rear of the vehicle.

The side pocket doors slide from front to rear.


### Steering Column Adjustment




### Seat Controls



Fore and Aft Adjuster




Height Adjuster



Recline Adjuster

## 5. Stored energy / liquids / gases / solids



12V  
Lead Acid



400V  
Li-ion



Damage to the battery pack can cause instability, and possibly a risk for a fire. Check the battery pack temperature using a thermal imaging camera.

## 6. In case of fire



A battery on fire will not explode.



Always wear Self-Contained Breathing Apparatus (SCBA).

Use copious amounts of water to cool the battery and to extinguish a fire.



Potential for Battery Re-Ignition.

**DO NOT CUT ANY ORANGE COLORED HIGH VOLTAGE CABLES.**

Identification Number

2G5-22101

Version Number

2

Page Number

Page 3 of 4



## 7. In case of submersion


The high voltage battery is isolated from the vehicle chassis. If the vehicle is immersed in water, there is no risk of electrocution by touching the vehicle.

After the vehicle was removed from the water, do the following:

1. Allow the vehicle to dry out.
2. Perform the high voltage disabling procedure in Section 3.

## 8. Towing / transportation / storage


Carefully open the cover in the fascia by using the small notch that conceals the tow eye socket.



Install the tow eye into the socket and turn it until it is fully tightened. When the tow eye is removed, reinstall the cover with the notch in the original position.

BrightDrop recommends a flatbed carrier or tow dollies to transport a disabled vehicle.

The lifting point features should only be used for lifting the vehicle. Do NOT use these features as attachment points to move or tie the vehicle down.



Moving the vehicle with the drive wheels on the ground will generate unwanted energy. Limit the movement of the vehicle to the distance required to prepare the vehicle for towing.

Store the vehicle a safe distance/separated from other vehicles.



Potential for continued hazards (rekindling/re-gassing/etc) if a damaged vehicle battery is jostled during recovery, including the towing and storage process.

## 9. Important additional information

This vehicle is supported by OnStar, where available.

## 10. Explanation of pictograms used

	Electric Vehicle		General warning sign		Warning, Electricity
	Battery Technology		Lifting Points		Thermal Imaging Camera
	Flammable		Toxic		Corrosive
	Injury Risk		Use Water		Cable Cut Location